

SMD High Current Inductor  
Size 2015

- I лЭK äI-údzNI-ə2y'ÖdzNIUSyú dzLJ ú2 млл !
  - [2Ø t2ääŠă ØлúK bI-ú ØлUS ŘŠăлЭY
  - [2Ø Ö2US t2ääŠă ØлúK a yÎy'Ö2US YI-úŠNIłI-f
  - vdzI-yəúëY мллLJÖă
- 
- I лЭK ÖdzNIUSyú 5 / κ5 / Ö2yØŠNIúŠNI
  - [ / ŨtúŠNI

Dimensions: [mm]

Land Pattern: [mm]



Electrical Properties:

hLJŠNI-əyЭ ¢SYLJŠNI-údzNISY ππл °C ú2 Ъмнр °C  
¢SYLJŠNI-údzNIS wIăŠ / dzNIUSyúŨ úKŠ I-ÖúdzI-f ØI-fdzŠ 2T 5 / ÖdzNIUSyú ØKŠY'úKŠ úSYLJŠNI-údzNIS NIăŠ Iă p¢πл °C  
{I-údzNI-ə2y' / dzNIUSyú úKI-ú Øłft ŐI-dzăŠ IyIəI-f IyŘdzŐúI-yŐŠ ú2 ŘNI2LJ I-LJLNI2ËIYI-úŠfê HđĤ:

Typical Electrical Characteristics:

